

Application

Diesel powered equipment from leading American manufacturers, including on-highway light and heavy-duty trucks and off-highway equipment for use in construction, mining, quarrying and agriculture. This product can also be utilized in two-cycle applications.

CUSTOMER BENEFITS

- **Defend** – These premium lubricants protect against oil thickening, high temperature deposits and corrosion
- **Perform** – AGRI-TEC 10 & 30 HEAVY DUTY ENGINE OILS minimize spot, rust, corrosion and sludge deposits, the primary causes behind premature engine failure and higher repair frequency
- **Extend Value Life** – Low sulfated ash content minimizes valve deposits extending valve life

FEATURES

AGRI-TEC 10 & 30 HEAVY DUTY ENGINE OILS are premium diesel engine oils blended from high quality base oils and a balanced additive system to meet or exceed the lubrication protection requirements of American diesel engine builders. They are specially formulated using a versatile blend of ashless dispersants, metallic detergents and inhibitor chemistry to control oxidation, wear, corrosion and rust.





AGRI-TEC 10 & 30 Heavy Duty Engine Oil

Values are typical and may vary within normal production ranges.

SAE Grade	10W	30W
Viscosity, ASTM D 445		
cSt @ 40°C	37.7	110
cSt @ 100°C	6.1	12.0
Viscosity Index, ASTM D 2270	107	98
Sulfated Ash, wt%, ASTM D 874	0.5	0.8
Total Base #, mg KOH/g, ASTM D 2896	4.0	7.3
Pour Point, °C, ASTM D 97	-30	-30
Flash Point, °C, ASTM D 92	232	258
Density @ 15°C kg/l, ASTM D 4052	0.877	0.892

