

Application

AGRI-TEC 15W40 HEAVY DUTY ENGINE OIL is designed for use in diesel and gasoline powered equipment, including turbo-charged models where high sulfur fuels are used.

- Newer low emission EGR/EPF diesel engines specifying the latest API service CJ-4/SM.
- Also recommended for older engines calling for API Service CI-4 Plus, CI-4, CH-4, CG-4, CF-4, CF-2, CF, CE, CD-II, CD/SG.
- MACK engines specifying MACK EO-o Premium Plus, EO-N Premium Plus, EO-M Plus, EO-M, EO-L Plus, EO-L and EO-K2 oils.
- Gasoline engines specifying up to API SM.
- Power shift transmissions specifying ALLISON C-3/C-4 and CAT TO-2 fluids.
- Mobile equipment hydraulic systems specifying engine oils.

CUSTOMER BENEFITS

- **Simplify Service** – AGRI-TEC 15W40 HEAVY DUTY ENGINE OIL is designed for use in diesel and gasoline powered equipment. The same product can be utilized across multiple equipment types to maximize service efficiency.
- **Maximize Engine Performance** – This special formulation minimizes spot, rust, corrosion and sludge deposits, the primary causes behind premature engine failure and higher repair frequency and reduced efficiency. The result is an equipment fleet that operates under maximum efficiency with consistency and reliability.
- **Extended Engine Life** – Special additives protect highly loaded parts from scuff, wear and premature failure, extending overall engine life, efficiency and equipment investment.

FEATURES

AGRI-TEC 15W40 HEAVY DUTY ENGINE OIL is formulated with premium quality base stocks and the most current additive technology to provide the highest equipment protection available. This heavy-duty engine oil is designed for all-season use in diesel and gas-mix powered equipment. It meets or exceeds the warranty and service requirements of virtually all diesel and gasoline engine manufacturers and is designed for today's high-performance, low-emission diesel engines that are equipped with Exhaust Gas Recirculation (EGR) and Diesel Particulate Filters. operating costs lowered by using this extended service fluid instead of conventional hydraulic fluid.





AGRI-TEC 15W40 Heavy Duty Engine Oil

Values are typical and may vary within normal production ranges.

Typical Properties	Typical
SAE Grade	15W40
Gravity, API @60°F	29.5
Color, ASTM	5.5
Viscosity:	
SUS @ 100°F	548
SUS @ 210°F	74.5
Flash Point °F	410
Pour Point °F	-25
Viscosity Index	120
Sulfated Ash, % Wgt.	1.17
Total Base Number (TBN)	12

