

Application

AGRI-TEC HT-II TRACTOR FLUID is a hydraulic and transmission fluid formulated to meet the requirements of International B-6 specifications as well as Case MS-1206 and their combination for MS-1207 field service.

CUSTOMER BENEFITS

- **Case/IH Alternative** – This superb formulation of solvent refined base oils is specifically designed for use in IH and Case-IH Tractors and equipment.
- **Enhanced Brake & Clutch Capabilities** – AGRI-TEC H-T II TRACTOR FLUID enhances brake and clutch capabilities while helping reduce brake chatter, clutch slippage and wear, and final drive wear.
- **Wear Protection** – This fluid provides superior wear protection for hydraulic components and drive train gears.
- **Controlled Frictional Characteristics** – Smooth operation of wet brakes and clutches is achieved with excellent frictional characteristics.

FEATURES

AGRI-TEC H-T II TRACTOR FLUID is a hydraulic and transmission fluid, fully formulated to meet the requirements of International B-6 specifications as well as Case MS-1206 and their combination for MS-1207 field service. Though intended to accommodate moisture, AGRI-TEC H-T II TRACTOR FLUID exhibits exceptional anti-rust and anti-corrosion properties. AGRI-TEC H-T II TRACTOR FLUID formulation contains all of the re-enforcing characteristics of a universal tractor fluid, including excellent wet-brake capability.



Values are typical and may vary within normal production ranges.

Physical Characteristics	Typical
Color	Amber
Gravity, API@60°F	29
Viscosity,	
SUS @100°F	21
SUS @210°F	51.4
cSt @ 40°C	45
cSt @ 100°C	7.6
Viscosity Index	135
Flash Point °F	360
Fire Point °F	380
Pour Point °F	-35

