



AGRI-TEC Passenger Car Motor Oil (5W30, 10W30, 10W40)

Application

AGRI-TEC PASSENGER CAR MOTOR OILS are formulated for gasoline passenger cars and light duty trucks.

- Performance Categories:
 - API Service SM, SL, SJ, SH
 - ILSAC Starburst GF-1, GF-2, GF-3 and GF-4

CUSTOMER BENEFITS

- **Superior Performance** – AGRI-TEC PASSENGER CAR MOTOR OILS provides outstanding wear protection to protect critical engine parts including those in turbo-charged engines that operate at high temperatures.
- **Improved Efficiency** – These product are specially formulated to prevent the formation of sludge and harmful deposits while improving fuel economy.
- **Maximize Engine Performance** – These special formulations minimizes soot, rust, corrosion and sludge deposits, the primary causes behind premature engine failure, higher repair frequency and reduced efficiency.
- **Warranty Protection** – These formulations satisfy the warranty requirements for today's passenger cars and light trucks that specify the ILSAC Starburst GF-1, GF-2, GF-3 and GF-4 engine oils.

FEATURES

AGRI-TEC PASSENGER CAR MOTOR OILS are high quality motor oils that incorporate anti-wear protection, as well as, protection against sludge and deposit formation.





AGRI-TEC Passenger Car Motor Oil (5W30, 10W30, 10W40)

Values are typical and may vary within normal production ranges.

SAE Grade	5W30	10W30	10W40
Sp. Gravity @ 15.6°C	0.860	0.872	0.8767
Viscosity: cSt @ 40°C	62	69	105.2
cSt @ 100°C	10.5	10.7	14.5
Viscosity Index	159	145	140
CCS Viscosity cP@-30°C	5500	6000	6000
Flash Point °C	200	210	405
Pour Point °C	-39	-36	-25
Color (ASTM)	2.5	3	4.5

